

APDatec 102 schwarz



Flexible hose made of soft PVC, reinforced with an impact-resistant hard PVC spiral.

Applications: Medium-weight suction hose for the water circuit on submersible on submersible and pond pumps in horticulture.

Imprint

with imprint

Durability

refer to Soft PVC

Colour

black

Food approval

No

REACH

conformity to 1907/2006/EC

RoHS

Conformity to Guideline 2015/863 (RoHS 3)

Spiral

Rigid-PVC

Material

Soft-PVC

empty

102.JPG

important advices

For proper use of our products please note

[Interesting facts about hoses](#)

All technical Data are according to ISO-Standard and at 20 °C ambient and medium temperature, technical changes reserved.

APDatec 102 schwarz

Nr.	Inside Diameter in mm	Outside Diameter in mm	Wall Thickness	Bending Radius	Working Pressure bar	Vacuum mmH2O	Length in m
102 019 0250 19	19	23,8	2,4	80	5	0,69	25
102 019 0500 19	19	23,8	2,4	80	5	0,69	50
102 025 0250 25	25	30	2,5	110	5	0,69	25
102 025 0500 25	25	30	2,5	110	5	0,69	50
102 032 0250 32	32	37,6	2,8	135	5	0,69	25
102 032 0500 32	32	37,6	2,8	135	5	0,69	50
102 038 0250 38	38	44,4	3,2	160	5	0,69	25
102 038 0500 38	38	44,4	3,2	160	5	0,69	50
102 040 0250 40	40	46,6	3,3	170	5	0,69	25
102 040 0500 40	40	46,6	3,3	170	5	0,69	50
102 050 0250 50	50	56,8	3,4	220	5	0,69	25
102 050 0500 50	50	56,8	3,4	220	5	0,69	50