

APDatec 120



Imprint

with imprint

Durability

refer to Polyesterurethane

Colour

transparent

Food approval

No

REACH

conformity to 1907/2006/EC

RoHS

Conformity to Guideline 2015/863 (RoHS 3)

Spiral

Rigid-PVC with Cooper

Material

Soft-PVC with PU-Liner

empty

120.JPG

important advices

For proper use of our products please note

Interesting facts about hoses

All technical Data are according to ISO-Standard and at 20 °C ambient and medium temperature, technical changes reserved.

APDatec 120

Nr.	Inside Diameter in mm	Outside Diameter in mm	Wall Thickness	Bending Radius	Working Pressure bar	Vacuum mmH2O	Length in m
120 032 0300	32	39	3,5	171	7	0,74	30
120 038 0300	38	45	3,5	180	7	0,74	30
120 040 0300	40	47,8	3,9	190	7	0,74	30
120 045 0300	45	53	4	212	6	0,69	30
120 051 0300	51	58,6	4	225	6	0,69	30
120 060 0300	60	68,4	4,2	270	6	0,69	30
120 065 0300	65	73,6	5,3	293	5	0,69	30
120 070 0300	70	79	4,5	316	5	0,69	30
120 075 0300	75	84,6	4,8	338	4	0,69	30
120 102 0200	102	114,6	6,3	459	3	0,69	20
120 127 0200	127	140,6	6,8	562	2	0,69	20