APDatec 273

Durability
SIEHE POLYESTER-PU

Colour
transparent

Food approval
No

REACH
conformity to 1907/2006/EC

RoHS
conformity to RoHs

Spiral
Spiral out of Steel

Material
Soft-PVC with PU-Liner

empty
27.jpg

APD Schlauchtechnik GmbH
Technologiering 12 | 41751 Viersen-Dülken | T +49 (0) 2163 9 49 96-0 | F +49 (0) 2163 9 49 96-29 | info@apd-schlauchtechnik.de

important advices

For proper use of our products please note

Interesting facts about hoses

All technical Data are according to ISO-Standard and at 20 °C ambient and medium temperature, technical changes reserved.

APDatec 273

Nr.	Inside Diameter in mm	Outside Diameter in mm	Wall Thickness	Bending Radius	Working Pressure bar	Vacuum mmH2O	Length in m
273 038 0200	38	47	4,5	152	6	0,93	20
273 040 0200	40	49,6	4,8	160	6	0,93	20
273 050 0200	50	60,8	5,4	200	6	0,93	20
273 060 0200	60	72	6	240	5	0,93	20
273 076 0200	76	88,4	6,7	300	4	0,93	20

APD Schlauchtechnik GmbH
Technologiering 12 | 41751 Viersen-Dülken | T +49 (0) 2163 9 49 96-0 | F +49 (0) 2163 9 49 96-29 | info@apd-schlauchtechnik.de