

APDatec 621



Durability

refer to Soft PVC

Colour

black

Food approval

No

REACH

conformity to 1907/2006/EC

RoHS

conformity to RoHs

Spiral

Spiral out of Steel

Material

Aluminium/Polyester

empty

621.JPG

important advices

For proper use of our products please note

Interesting facts about hoses

All technical Data are according to ISO-Standard and at 20 °C ambient and medium temperature, technical changes reserved.

APDatec 621

Nr.	Inside Diameter in mm	Outside Diameter in mm	Wall Thickness	Bending Radius	Vacuum mmH2O	Length in m
621 051 51	51	52	0,2	25	0,12	10
621 063 63	63	64	0,2	31	0,11	10
621 076 76	76	78	0,2	38	0,09	10
621 080 80	80	82	0,2	40	0,09	10
621 090 90	90	92	0,2	45	0,08	10
621 102 102	102	104	0,2	51	0,08	10
621 127 127	127	129	0,2	63	0,06	10
621 152 152	152	154	0,2	76	0,05	10
621 160 160	160	162	0,2	80	0,04	10
621 180 180	180	182	0,2	90	0,02	10
621 203 203	203	205	0,2	101	0,02	10
621 254 254	254	256	0,2	127	0,01	10
621 305 305	305	307	0,2	152	0,01	10
621 356 356	356	358	0,2	178	0,01	10
621 408 408	408	410	0,2	204	0,01	10
621 459 459	459	461	0,2	229	0,01	10
621 510 510	510	512	0,2	255	0,01	10
621 610 610	610	612	0,2	305	0,005	10