

## APDatec 630 gelb



**Durability**

refer to Soft PVC

**Colour**

yellow

**Food approval**

No

**REACH**

conformity to 1907/2006/EC

**RoHS**

conformity to RoHs

**Spiral**

Spiral out of Steel

**Material**

PVC-beschichtetes Polyestergewebe

**\_empty\_**

630.JPG

#### important advices

For proper use of our products please note

#### Interesting facts about hoses

All technical Data are according to ISO-Standard and at 20 °C ambient and medium temperature, technical changes reserved.

## APDatec 630 gelb

| Nr.     | Inside Diameter in mm | Outside Diameter in mm | Wall Thickness | Bending Radius | Vacuum mmH2O | Length in m |
|---------|-----------------------|------------------------|----------------|----------------|--------------|-------------|
| 630 125 | 152                   | 157                    | 0,25           | 76             | 0,1          | 7,6         |
| 630 152 | 152                   | 157                    | 0,25           | 76             | 0,1          | 7,6         |
| 630 203 | 203                   | 208                    | 0,25           | 101            | 0,1          | 7,6         |
| 630 254 | 254                   | 259                    | 0,25           | 127            | 0,1          | 7,6         |
| 630 305 | 305                   | 310                    | 0,25           | 153            | 0,1          | 7,6         |
| 630 425 | 425                   | 430                    | 0,25           | 212            | 0,1          | 7,6         |
| 630 525 | 525                   | 530                    | 0,25           | 262            | 0,1          | 7,6         |
| 630 600 | 600                   | 605                    | 0,25           | 305            | 0,08         | 7,6         |
| 630 650 | 650                   | 655                    | 0,25           | 0,08           | 7,6          |             |
| 630 700 | 700                   | 705                    | 0,25           | 350            | 0,05         | 7,6         |