

APDatec 636



Colour

transparent

Food approval

No

REACH

conformity to 1907/2006/EC

RoHS

conformity to RoHs

Spiral

Clamping profil out of galvanised steel

Material

Polyurethan foil

empty

636.JPG

important advices

For proper use of our products please note

Interesting facts about hoses

All technical Data are according to ISO-Standard and at 20 °C ambient and medium temperature, technical changes reserved.

APDatec 636

Nr.	Inside Diameter in mm	Bending Radius	Working Pressure bar	Vacuum mmH2O
636 0050	50	50	0,5	0,37
636 0060	60	59	0,441	0,26
636 0075	75	74	0,337	0,17
636 0080	80	82	0,312	0,15
636 0100	100	92	0,239	0,09
636 0120	120	110	0,192	0,07
636 0125	125	115	0,183	0,06
636 0140	140	125	0,16	0,05
636 0150	150	129	0,147	0,04
636 0160	160	133	0,136	0,04
636 0180	180	150	0,118	0,03
636 0200	200	191	0,104	0,02
636 0250	250	239	0,08	0,02
636 0300	300	286	0,064	0,01
636 0350	350	334	0,053	0,01
636 0400	400	320	0,045	0,01
636 0500	500	400	0,035	0,004
636 0600	600	480	0,028	0,003