

APDatec 916



Ideal for transporting sensitive and aggressive liquids and media in industry, chemicals, food and medical technology

Excellent chemical resistance, anti-adhesive and low friction, excellent dielectric properties, no water absorption, UV and weather resistant, flame resistant. Physiological harmlessness, food contact compliant according to EC2002/72 DM174/2004, REACH according to 1907/2006/EC, RoHS according to 2011/65/EU.

Imprint

with imprint

Durability

refer to Polyflourethylene

Colour

natur

Food approval

conformity to EC2002/72 DM174/2004

REACH

conformity to 1907/2006/EC

RoHS

conformity to RoHS

Material

PTFE: Polytetrafluorethylen

empty

916.JPG

important advices

For proper use of our products please note

Interesting facts about hoses

All technical Data are according to ISO-Standard and at 20 °C ambient and medium temperature, technical changes reserved.

APDatec 916

Nr.	Inside Diameter in mm	Outside Diameter in mm	Wall Thickness	Working Pressure bar	Bursting Pressure bar	Length in m
916 004 10 00 2	4	4	1	42	127	100
916 005 10 50 3	5	5	1	32	95	50
916 006 10 50 4	6	6	1	20	60	50
916 006 10 00 4	6	6	1	20	60	100
916 008 15 50 5	8	8	1,5	29	88	50
916 008 10 50 6	8	8	1	13	39	50
916 008 10 00 6	8	8	1	13	39	100
916 010 10 50 8	10	10	1	10	30	50
916 009 08 50 8	9	9	0,85	10	30	50
916 012 15 50 9	12	12	1,5	14	42	50
916 012 10 50 10	12	12	1	9	27	50
916 014 10 50 12	14	14	1	7	21	50