

Goldschlange



The Goldschlange® is a rubber hose with a black, pore- pore-free, smooth EPDM inner layer and black, fabric-patterned CR outer layer.

It is resistant to ozone, weathering, UV, oil, grease, chemicals and abrasion. It can be steamed up to +130°C (max. 30 minutes). Kink- and shock-resistant, can be driven over. 5-year warranty.

Applications: GOLDSCHLANGE® is the right hose for demanding applications. Such as in construction, in the open air or on machines, apparatus, containers.

Imprint

with imprint

Durability

SIEHE EPDM

Colour

black with yellow wave stripe

Yarn

Polyester fabric

Food approval

No

REACH

conformity to 1907/2006/EC

RoHS

Conformity to Guideline 2015/863 (RoHS 3)

Material

EPDM/CR

empty

268.JPG

important advices

For proper use of our products please note

[Interesting facts about hoses](#)

All technical Data are according to ISO-Standard and at 20 °C ambient and medium temperature, technical changes reserved.

Goldschlange

Nr.	Inside Diameter in mm	Outside Diameter in mm	Wall Thickness	Bending Radius	Working Pressure bar	Bursting Pressure bar	Length in m	Weight per Piece
268 010 40	10	17,2	3,6	45	30	90	40	6,4
268 013 40	13	20,8	3,9	50	30	90	40	9
268 016 40	16	23,2	3,6	70	25	75	40	10,4
268 019 40	19	27,8	4,4	80	25	75	40	15,4
268 022 40	22	31	4,5	100	20	60	40	17,2
268 025 40	25	34	4,5	160	20	60	40	19,6
268 032 40	32	43	5,5	175	12	36	40	30,4
268 038 40	38	51	6,5	250	12	36	40	42
268 050 40	50	65	7,5	300	10	30	40	63,2