

PleXus AT mit Armaturen

Imprint

with imprint

Durability

SIEHE WEICH-PVC

Colour

yellow with orange stripe

Yarn

Polyester fabric

Food approval

No

REACH

conformity to 1907/2006/EC

RoHS

Conformity to Guideline 2015/863 (RoHS 3)

empty

834K.jpg

Material

Soft-PVC

important advices

For proper use of our products please note

[Interesting facts about hoses](#)

All technical Data are according to ISO-Standard and at 20 °C ambient and medium temperature, technical changes reserved.

PleXus AT mit Armaturen

Nr.	Inside Diameter in mm	Outside Diameter in mm	Wall Thickness	Working Pressure bar	Bursting Pressure bar	Length in m	Connection Fitting	Weight per Piece
834 013 0250 K	12,5	16,8	2,15	10	30	25	Brass Claw Coupling	3,5
834 013 0500 K	12,5	16,8	2,15	10	30	50	Brass Claw Coupling	6,9
834 019 0250 K	19	24,4	2,7	7	21	25	Brass Claw Coupling	6,3
834 019 0500 K	19	24,4	2,7	7	21	50	Brass Claw Coupling	12,3
834 025 0250 K	25	31,6	3,3	6	18	25	Brass Claw Coupling	10,5
834 025 0500 K	25	31,6	3,3	6	18	50	Brass Claw Coupling	20,3