

PleXus AT



Description: 4-ply PVC hose, UV and ozone resistant, free from algae formation, phthalate free, high tenacity polyester yarn with spiralized tricot fabric technology, which actively prevents the hose from twisting.

Features: Very handy, excellent flexibility even at low temperatures, no soft layers of foamed PVC, high resistance to kinking and crushing.

Applications: For gardening and irrigation and professional use in GALA construction and plant cultivation.

Imprint

with imprint

Durability

SIEHE WEICH-PVC

Colour

yellow with orange stripe

Yarn

Polyester fabric

Food approval

No

REACH

conformity to 1907/2006/EC

RoHS

Conformity to Guideline 2015/863 (RoHS 3)

empty

834.jpg

Material

Soft-PVC

important advices

For proper use of our products please note

[Interesting facts about hoses](#)

All technical Data are according to ISO-Standard and at 20 °C ambient and medium temperature, technical changes reserved.

PleXus AT

Nr.	Inside Diameter in mm	Outside Diameter in mm	Wall Thickness	Working Pressure bar	Bursting Pressure bar	Length in m	Weight per Piece
834 013 0250	12,5	16,8	2,15	10	30	25	3,25
834 013 0500	12,5	16,8	2,15	10	30	50	6,5
834 019 1000	19	24,4	2,7	7	21	100	23
834 019 0500	19	24,4	2,7	7	21	50	11,5
834 019 0250	19	24,4	2,7	7	21	25	5,75
834 025 1000	25	31,6	3,3	6	18	100	39
834 025 0250	25	31,6	3,3	6	18	25	9,75
834 025 0500	25	31,6	3,3	6	18	50	19,5